

Sa loob ng mahigit na **40 taon**, ang **ADA Manufacturing Corporation (ADAMCO)** ay nagsilbing katuwang sa pag-unlad ng mga magsasaka, negosyante at pamilyang Pilipino.

Sa **ADAMCO** maaring magka-negosyo at kumita ng malaki at madali!

THE ONLY DEALER OF
YANMAR
IN THE PHILIPPINES

RICE/CORN COMBINE HARVESTER
TRACTOR
RICE TRANSPLANTER

Mga produktong mapagkakakitaan mula sa

ADAMCO:

- SPARE PARTS
- TRAILER
- TRAILER BEDS
- TRACTOR IMPLEMENTS

NATIONWIDE BRANCHES

- TUGUEGARAO, CAGAYAN
- NAGUILIAN, ISABELA
- CAUAYAN CITY, ISABELA
- SANTIAGO CITY, ISABELA
- SOLANO, NUEVA VIZCAYA
- MUÑOZ, NUEVA ECIJA
- CABANATUAN, NUEVA ECIJA
- JAEN, NUEVA ECIJA
- URDANETA, PANGASINAN
- TARLAC CITY, TARLAC
- PULILAN, BULACAN
- CALAPAN, ORIENTAL MINDORO
- NAGA CITY, CAMARINES SUR
- JARO, ILOILO
- SARA, ILOILO
- PALO, LEYTE
- GENERAL SANTOS CITY
- MATINA PANGI, DAVAO CITY
- KORONADAL, SOUTH COTABATO
- KAUSWAGAN, CAGAYAN DE ORO



ADAMCO
Kita tayo dito!

YANMAR
RICE/CORN COMBINE HARVESTERS



Mapagagaan ang pagbili ng produkto gamit ang **Special Financing Scheme** mula sa partner banks ng **ADAMCO**



FOR INQUIRIES, CONTACT US AT:

0917 323 2626

adamcoph | www.adamco.ph

Panalo ka sa paggamit ng HARVESTER!

**YANMAR
AW70V**

5 Hectares
kada araw



**YANMAR
AW82V**

6 Hectares
kada araw



**Pinag-isa ang anim na proseso
(6-in-1) Process**

- Paggapas o Reaping
- Pag-iipon ng ginapas o Gathering
- Pagbubuhat
- Paggiik o Threshing
- Paglilinis o Cleaning
- Pagsasako o Bagging

TECHNICAL SPECIFICATIONS

MODEL		AW70V HIGH CLEARANCE		AW82V HIGH CLEARANCE		
Dimensions	Length	mm	5,030	5,030		
	Width	mm	2,285	2,285		
	Height	mm	2,905	2,905		
Weight		kg	3,160	3,195		
Engine	Model name	YANMAR 4TNV98		YANMAR 4TNV98 Turbo		
	Type	Water-cooled 4-cycle 4-cylinder vertical direct injection diesel				
	Total displacement	cc	3,318	3,318		
	Maximum output	PS/rpm	70.0 / 2,500	82.0 / 2,400		
	Fuel tank capacity	ℓ	90	90		
	Starting mode	Electric start				
Traveling Section	Crawler	Width x Grounding length	mm 500 x 1,700			
	Mode of speed control	HST side clutch hydraulic type				
	Range shift gear	3 ranges				
	Traveling speed	Low speed	m/sec	0 ~ 0.93	0~0.95	
		Middle speed	m/sec	0 ~ 1.50	0~1.55	
High speed		m/sec	0 ~ 1.86	0~1.91		
Reaping Section	Min. Ground clearance	mm	327			
	Gap at the front end of crop divider	mm	2060			
	Cutter blades width	mm	1975			
	Cutting height range	mm	-50 ~ 1,000			
	Reel	Diameter x Width	mm	900 x 1,920		
Threshing Section	Type	Double rotor system (Front rotor + Axial-flow type threshing rotor)				
	Front rotor	Diameter x Width	mm	400 x 520		
	Threshing rotor	Diameter x Width	mm	640 x 1,850		
	Swing separator (selection)	mm	850 x 1,410			
	Concave size	m ²	1.75			
Grain Output	Method	2 Grain Output (Top sucker 2 ports)				
	Tank or hopper capacity	ℓ	490			

*Specifications in this catalogue are subject to change without prior notice.



***With CORN-KIT
ATTACHMENT
available**

- **MALAKAS ANG ENGINE**
- **MALINIS ANG ANI**
- **MAGANDA ANG KITA**