

Sa loob ng mahigit na **40 taon**, ang **ADA Manufacturing Corporation (ADAMCO)** ay nagsilbing katuwang sa pag-unlad ng mga magsasaka, negosyante at pamilyang Pilipino.

Sa **ADAMCO** maaring magka-negosyo at kumita ng malaki at madali!

THE ONLY DEALER OF  
**YANMAR**  
IN THE PHILIPPINES

RICE/CORN COMBINE HARVESTER  
TRACTOR  
RICE TRANSPLANTER

Mga produktong mapagkakakitaan mula sa

**ADAMCO:**

- SPARE PARTS
- TRAILER
- TRAILER BEDS
- TRACTOR IMPLEMENTS

**NATIONWIDE BRANCHES**

- TUGUEGARAO, CAGAYAN
- NAGUILIAN, ISABELA
- CAUAYAN CITY, ISABELA
- SANTIAGO CITY, ISABELA
- SOLANO, NUEVA VIZCAYA
- MUÑOZ, NUEVA ECIJA
- CABANATUAN, NUEVA ECIJA
- JAEN, NUEVA ECIJA
- URDANETA, PANGASINAN
- TARLAC CITY, TARLAC
- PULILAN, BULACAN
- CALAPAN, ORIENTAL MINDORO
- NAGA CITY, CAMARINES SUR
- JARO, ILOILO
- SARA, ILOILO
- PALO, LEYTE
- GENERAL SANTOS CITY
- MATINA PANGI, DAVAO CITY
- KORONADAL, SOUTH COTABATO
- KAUSWAGAN, CAGAYAN DE ORO



**ADAMCO**  
**Kita tayo dito!**

Mapagagaan ang pagbili ng produkto gamit ang **Special Financing Scheme** mula sa partner banks ng **ADAMCO**



**YANMAR**  
**FARM TRACTORS**



FOR INQUIRIES, CONTACT US AT:

**0917 323 2626**

**adamcoph** | **www.adamco.ph**

## YANMAR EF393T

3 Hectares  
kada araw



## YANMAR EF514T

5 Hectares  
kada araw



## YANMAR EF725T

7 Hectares  
kada araw



Model		EF393T	
Engine	Make	Yanmar	
	Model	3TNV88	
	Type	Direct injection, Water cooled, diesel	
	Output	SAE Gross (ps)	39.0
Dimension	Rated RPM	(rpm)	2800
	No. of cylinders		3
	Displacement	(cc)	1,642 cc
	Fuel tank	(lit.)	38
Weight	Overall length	(mm)	2940
	Overall width	(mm)	1430
	Overall height (steering wheel)	(mm)	1950 (1400)
	Tread	Front (mm)	1065
		Rear (mm)	1120
Tire size	Wheelbase	(mm)	1650
	Ground clearance	(mm)	320
Steering	Weight	(kg)	1090
	Tire size	Front	8 - 16
Clutch	Weight	Rear	12.4 - 24
	Steering	Hydrostatic power steering	
Transmission	Brake	Wet multi-disc type	
	Clutch	Dry single	
Turning radius	No. of shifting gears	8 forward and 8 reverse (constant mesh)	
	Reverser	Synchro-mesh	
PTO	Travel speed	Forward (km/hr)	1.90 - 21.1
	Reverse (km/hr)		1.84 - 21.9
Hydraulic system	Turning radius (with brake)	(m)	2.4
	Gear 1	584 rpm (at engine speed: 2800rpm)	
Drawbar hitch	Gear 2	836 rpm (at engine speed: 2800rpm)	
	Type	Position control	
Hydraulic	Hitch	3-point hitch	
	Category	Category 1	
Drawbar hitch	Max. lifting capacity (at lower link end)	(kg)	925
	Hydraulic pump capacity	(lit./min)	20.2

MODEL		EF514T	
Dimensions	Drive type	4-wheel Drive	
	Overall length (mm)	3,230	
	Overall width (mm)	1,605	
	Overall height (mm)	2,355	
Weight (kg)	Wheelbase (mm)	1,830	
	Tread	Front (mm)	1,300, 1,550
		Rear (mm)	1,270, 1,350
	Ground clearance (mm)	375	
Engine	Model	4TNV88	
	Type	4-cycle, water-cooled diesel	
	Output (SAE Gross) (HP/rpm)	51/2,800	
	Number of cylinders	4	
	Bore x Stroke (mm)	88 x 90	
	Displacement (cc)	2,190	
	Air cleaner	Dry, dual element	
	Fuel tank capacity (liter)	40	
Steering	Battery	12V-52AH	
	Steering	Hydrostatic	
Clutch	Clutch	Dry, single	
	Brake	Mechanical, wet disc	
Transmission	Type	Constant mesh	
	Gear shift (Forward x Reverse)	F9 x R9	
	Forward speed (km/hr)	1.6-28.8	
	Reverses speed (km/hr)	1.7-29.7	
Tire	Max. speed, forward (km/hr)	30.8	
	Front	8-18	
Rear PTO	Rear	13.6-26	
	Type	Transmission PTO	
Hydraulic	PTO shaft	SAE1-3/8 inch (35mm), 6 spline	
	Speed (rpm)	568, 769 at rated engine speed	
Drawbar hitch	Type	Position control	
	Hitch	3 point hitch, category SAE #1	
Drawbar hitch	Type	Clevis type	

MODEL		EF725T	
Dimensions	Drive type	4-wheel Drive	
	Overall length (mm)	3,670	
	Overall width (mm)	1,865	
	Overall height (mm)	ROPS 2,600, Canopy 2,620	
Weight (kg)	Wheelbase (mm)	2,050	
	Tread	Front (mm)	1,420, 1,535
		Rear (mm)	1,440, 1,500, 1,615, 1,725
	Ground clearance (mm)	450	
Engine	Weight (kg)	2,250	
	Model	4TNV98-NRY1C	
	Type	4-cycle, water-cooled diesel	
	Output (SAE Gross) (HP/min <sup>1</sup> )	72/2,500	
	Number of cylinders	4	
	Bore x Stroke (mm)	98 x 110	
	Displacement (cc)	3,319	
	Air cleaner	Dry, dual element and pre-cleaner	
Steering	Fuel tank capacity (liter)	70	
	Battery	12V-72AH	
Clutch	Steering	Hydrostatic	
	Clutch	Dry, single	
Transmission	Brake	Mechanical, wet disc	
	Type	Synchro-shuttle	
Tire	Gear shift (Forward x Reverse)	F8 x R8	
	Forward speed (km/hr)	2.9-31.8	
	Reverses speed (km/hr)	3.0-32.4	
	Max. speed, forward (km/hr)	34.7	
Rear PTO	Front	9.5-24-6	
	Rear	16.9-30-8	
Hydraulic	Type	Transmission PTO	
	PTO shaft	SAE 1-3/8 inch (35mm), 6 spline	
Drawbar hitch	Speed (min <sup>1</sup> )	540/2409, 720/2287	
	Type	Draft Position control	
Drawbar hitch	Hitch	3 point hitch, category SAE #2	
	Type	Swing drawbar type	

## TECHNICAL SPECIFICATIONS

\*Specifications in this catalogue are subject to change without prior notice.