

YANMAR

YH SERIES - YH850



MAS MABILIS

- Steering wheel; Car-like operation



MAS MALINIS ANG ANI

- Double threshing system



MAS KAUNTI ANG TAPON

- Long threshing drum (1,850mm)



MALAKAS AT DI BALAHUIN

- 85 horsepower engine
- High ground clearance at 420mm



SIGURADO ANG KITA

- Monitor machine work, location and status 24/7
- Measure actual field size serviced



INSTRUMENT PANEL



ADJUSTABLE SEAT



STEERING WHEEL



WIDE SWING SEPARATOR



WIDE AND LONG CRAWLER



- ✓ Steering Wheel
- ✓ Mas malakas at di balahuin
- ✓ Wide & High Clearance
- ✓ Mas kaunti ang tapon
- ✓ Double threshing kaya mas malinis ang ani
- ✓ Can harvest up to 6.5 hectares per day



A

NGAT SA BILIS



G

ANADO KA SA PERFORMANCE



R

EQUEST NG MAGSASAKA



I

INVESTMENT NA ABOT-KAYA

YANMAR
EXCLUSIVE DEALER
IN THE PHILIPPINES

SMARTASSIST
Agribusiness Anywhere. Anytime.
Everywhere.

GPS Measure Lot Size

YANMAR
GENUINE SPAREPARTS

YH850 COMBINE HARVESTER TECHNICAL SPECIFICATIONS



MODEL		YH850W-PH		
Machine size	Overall Length (mm)	5,070		
	Overall Width (mm)	2,285		
	Overall Height (mm)	2,930		
Weight	(kg)	3,365		
Engine	Model name	4TNV98T		
	Type	4-cylinder, Water-cooling, single-row, vertical, 4-stroke		
	Total displacement (cc)	3,318		
	Max Output kW(PS/rpm)	62.1 (84.5) / 2,500		
	Fuel used	Diesel fuel		
	Fuel tank capacity (L)	115		
Starting system		Self-Starter		
Travelling Section	Track	Width x Grounding length (mm)	550 x 1,700	
		Center distance (mm)	1,185 (between sprockets, 1,185)	
		Average ground-ing pressure (kPa)	17.6	
	Mode of speed regulation	HST (with Hydraulic servo), FDS		
	Shift gear	3 gears		
	Traveling Speed (under the rated engine speed) (m/s)	Low: 0 - 1.00 Standard: 0 - 1.55 High: 0 - 2.09		
	Min. ground clearance	420		
Header	Gap at the front end of crop divider (mm)	2,060		
	Type of harvesting device (mm)	Reel + Platform		
	Cutter blade width (mm)	1,975		
	Stubble range (mm)	-80 ~ 1,020		
	Reel	Diameter x Width (mm)	900 x 1,920	
		Revolving speed (rpm)	44 (55)	
Threshing Section	Type	Axial-flow type longitudinally mounted front roller		
	Roller	Diameter x Width (mm)	640 x 1,850	
		Revolving speed (rpm)	575 (19.3 m/s)	
	Mode of screening	Vibration, Air blast, Secondary reduction		
	Screening width (mm)	850		
	Screening plate (width x length)	850 x 1,410		
Mode of secondary reduction	Grain conveying pipe and vibrating screen			
Concave screen area (m ²)	1.75			

AVAILABLE ATTACHMENTS



CORN KIT



TRAILER BED

NOTE: Specifications are subject to change without prior notice.

0917-3AD-AMCO
0917-323-2626

0917-7AD-AMCO
0917-723-2626

f adamcoph

www.adamco.ph