YANMAR

EF SERIES - EF393T



PINO ANG BUNGKAL

- 39 Horsepower engine - With 48 Rotary blades



MAARING PAGKAKITAAN BUONG TAON

- 925kgf hydraulic lift capacity
- Variety of implements are available to perform different tasks and earn profit all year round



MABILIS

- Lightweight (1090kg)





AVAILABLE IMPLEMENTS



























EQUEST NG MAGSASAKA





NVESTMENT NA ABOT-KAYA



0917-7AD-AMCO 0917-723-2626





MODEL				EF393T
	Make			Yanmar
Engine	Model			3TNV88
	Туре			Direct injection, Water cooled, Diesel
	Output	SAE Gross	s (cc)	39.0
	Rated RPM (rpm)		(rpm)	2800
	No. of cylinders			3
	Displacement (cc)			1,642 cc
	Fuel Tank (lit.)		(lit.)	38
Dimension	Overall length (mm)		(mm)	2940
	Overall width (mm)			1430
	Overall height (steering (mm)			1950 (1400)
	Tread	Front	(mm)	1065
		Rear	(mm)	1120
	Wheelbase (mm)		(mm)	1650
	Ground clearance (mm)			320
Weight (kg)				1090
Tire Size	Front			8 - 16
Tire Size	Rear			12.4 - 24
Steering				Hydrostatic power steering
Brake			Wet multi-disc type	
Clutch			Dry single	
Transmission	No. of shifting gears			8 forward and 8 reverse (constant mesh)
	Reverser			Synchro mesh
	Travel Speed	Forward	(km/hr)	1.90 - 21.1
		Reverse	(km/hr)	1.84 - 21.9
Turning radius (with brake) (m)			2.4	
DTO	Gear 1			584 rpm (at engine speed: 2800 rpm)
PTO	Gear 2			836 rpm (at engine speed: 2800 rpm)
Hydraulic System	Туре			Position control
	Hitch			3-point hitch
	Category			Category 1
	Max. lifting capacity (at lower link end) (kg)			925
	Hydraulic pump capacity (lit./min)			20.2





NOTE: Specifications are subject to change without prior notice.



